XLNT C-Power™ Stromverteilung für XLNT CyberMotion™

C-POWER®

XLNT C-Power™

DS4 CM H
DS8 CM L
Stromverteilung

Halbleiterstromverteiler für die XLNT CyberMotion™ Produktpalette

- Optimierte Konstruktion für die anspruchsvollsten Anforderungen in der Entertainmentindustrie
- Robustes, langlebiges Stahlgehäuse
- Komponenten in industrieller Qualität
- Mit den geltenden internationalen Sicherheitsstandards konform (EN60947/EN60204)
- Sicher und zuverlässig: Individuelle Leitungsschalter und thermischer Schutz pro Kanal

Teil der XLNT CyberMotion™ Familie:
CyberHoist II™
C-Hoist™
C-Winch™
C-Track™ & C-Trolley™
C-Power™
MotionCue3D™

CYBERMOTION®

xlnt advanced technologies

TECHNISCHE MERKMALE:

Optimierte Konstruktion als Stromquelle des CyberMotion - Systems in der Entertainmentindustrie

C-Power™ wurde insbesondere für die CyberMotion™ Produktpalette entwickelt. Besonderes Augenmerk galt hierbei den spezifischen Anforderungen in der Entertainmentindustrie beim weltweiten Einsatz auf Tourneen: Optimierte Konstruktion auf der Grundlage praktischer Erfahrungen und entsprechend der Anforderungen von Unternehmen in der Bühnentechnik.

Die Plug&Play-Stromverteiler-Racks und Breakoutboxen können mit mehreren Spannungen betrieben werden und sind für einen weltweiten Einsatz mit gängigen Ein- und Ausgangssteckern ausgestattet.

Wichtigste Merkmale

Sofort einsatzbereit und langlebig:

- Optimierte Konstruktion für die spezifischen Anforderungen in der Entertainmentindustrie
- Robustes Stahlgehäuse für eine fortwährende Qualität und Langlebigkeit
- Netzanschluss mit Autorange-Funktion für den weltweiten Einsatz (200-440V +/- 10%, 50/60 Hz) mit gängigen Ein- und Ausgangssteckern
- Komponenten in industrieller Qualität

Sicherer und einfacher Betrieb:

- Individuelle Leistungsschalter pro Kanal
- Thermischer Schutz pro Kanal
- Hauptschütz und Netzschalter mit Stromanzeige-LED

Technische Daten

	DS4 CM H	DS8 CM L
Max. Motorleistung pro Kanal	10 A	10 A
Eingangsspannung	(200-440V +/- 10%, 50/60 Hz)	
Eingangsanschluss	Harting 80A oder pigtail für USA version	
Ausgangsanschluss*	1 x Harting HAN16 Modular oder 419P Socapex*	2 x Harting H16 Modular oder 419P Socapex*
Rahmengröße	19" – 5HE	
Abmessungen (HxBxT)	223 x 483 x 300mm (8.78" x 19.02" x 11.81")	

* Socapex 419 für nur USA versionen

XLNT C-Power™ Power distribution for XLNT CyberMotion™

C-POWER®

XLNT C-Power™

DS4 CM H
DS8 CM L
Power Distribution

Power distribution for the XLNT CyberMotion™ product range

- Dedicated design meeting the most demanding entertainment requirements
- Road-proof, durable steel housing
- Industrial grade components
- Compliant with applicable international safety standards (EN60947/EN60204)
- Safe and reliable: Individual circuit breakers and thermal protection per channel

Part of the XLNT CyberMotion™ family:

CyberHoist II™
C-Hoist™
C-Winch™
C-Track™ & C-Trolley™
C-Power™
MotionCue3D™

CYBERMOTION®

xlnt advanced technologies

TECHNICAL FEATURES:

Dedicated entertainment design to power XLNT CyberMotion™

C-Power™ was developed especially for the CyberMotion™ product range, according to the specific needs within the entertainment industry for global touring: A dedicated design based on the practical experience and requirements of leading riggers.

The plug and play power distribution racks and breakout boxes are multi-voltage and designed for world-wide use with common available in- and output connectors.

Key Features

Road-proof durability:

- Dedicated design meeting specific entertainment industry requirements
- Robust steel housing for road-proof, durable quality
- Auto ranging input voltage for global use (175-440V, 50/60 Hz) using common in and output connectors
- Industrial grade components

Safety and easy operation:

- Individual circuit breaker per channel
- Thermal protection per channel
- Main contactor and On/Off switch with LED power indicator

Specifications

	DS4 CM H	DS8 CM L
Motor power Max per channel	10 Amp	10 Amp
Input voltage	175-440 V – 50/60 Hz	
Input connection	Harting 80Amp or pigtail for US version	
Output connection*	1 x Harting HAN16 Modular or Socapex 419P*	2 x Harting H16 Modular or Socapex 419P*
Frame size	19" – 5HE or pigtail for US version	
Dimensions (HxWxD)	223 x 483 x 300mm (8.78" x 19.02" x 11.81")	

* Socapex 419 on US versions only

XLNT Advanced Technologies BV, Proostwetering 50, 3543 AH Utrecht (The Netherlands) - Tel. (+31/ 0)30 247 9999 - Fax (+31/ 0)30 247 9998 - info@xlnt-at.com - www.xlnt-at.com